

Make a statement with Mono Stringer.

- ✓ Custom design solution
- √ 2 to 17 tread configurable
- ✓ Interior or exterior projects
- ✓ Choice of finish treatments
- ✓ Step-by-step installation
- Complies with the NCC[^]



Build now with ready made Dual Stringers.

- ✓ Simple to configure for all project types
- √ 1 to 17 treads ready made
- √ Hot-dip galvanised to AS/NZS 4680:2006 for maximum corrosion resistance.
- ✓ Easy to install via concrete cast-in or optional bolt-down bracket
- ✓ Fits 1000mm wide treads Pairs with optional steel stair treads.
- ✓ Complies with the NCC^ˆ when a minimum tread height of 50mm is used.
- ✓ Complies with AS1657:2018, engineered to the requirements of AS1170.1:2002 (up to a UDL of 4.0kPa and a point load of 4.5kN).





Call 1800LINTEL or visit galintel.com.au

© Copyright 2023 NEPEAN Building & Infrastructure [ABN 54 125 224 302]. A division of NEPEAN. Galintel is a registered Trade Mark of Ronald E Graham (Holdings) Ptv Ltd. Galintel Mono Stringer is certified Australian Made and Owned. ^ Products comply with the requirements of the National Construction Code Volume 2 for Class 1 and 10 buildings Part 3.9.1 when installed with treads at least 50mm thick. The minimum 50mm thick tread is to meet the dimensional requirements of Figure 3.9.1.4 to prevent a 125mm sphere from passing between the treads. Refer to galintel.com.au for more details, [03/2023]

